14000-Watt Gasoline

This portable generator is built to withstand the most demanding work conditions and can easily be transported from job site to job site.







Alternator

- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame

- Reinforced 11/4-inch powder coated steel tube frame
- Flat-free tires

Components

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone mufflers
- Easy-to-read fuel gauge
- Idle control
- Voltmeter/hour meter
- Heavy-duty industrial air cleaner

Miscellaneous

- USDA/USFS-approved spark arrestors

















NEMA L14-30R



Model Number	GEN-14000-1MHE		
Max. AC Output	14000 watts		
Rated AC Output	12000 watts		
Displacement/Engine	688cc Honda GX630 OHV with electric start - battery included		
Frequency/Voltage	Brushless 120V/240V, 60Hz		
Max. Amps (120V/240V)	116.7/58.3		
Cont. Amps (120V/240V)	100.0/50.0		
Receptacles	(2) 120V, 20A GFCI duplex, (1) 120V, 30A twist lock, (1) 120V/240V, 30A twist lock, (1) 120V/240V, 50A		
Circuit Breakers	(2) 20A toggle circuit breakers, single pole, (1) 30A toggle circuit breaker, single pole, (1) 30A toggle circuit breaker, double pole, (1) 50A toggle circuit breaker, double pole		
Rated Speed	3600 RPM		
Decibel Rating	77.5		
Fuel Capacity	13.2 gallons		
Run Time (At Full Load)	8.0 hours		
Dimensions (LxWxH)	31.5x30.5x37.5in.		
Ship Wt.	568 lb.		
Net Wt.	508 lb.		

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

Accessories & Options:		
Part Number	Description	Fits Model
32-0915	RV generator adapter - 30A/125V female/male; use to connect RV cordsets to 30A generators	GEN-14000-1MHE
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	GEN-14000-1MHE
GX-0003	Skid feet - Stationary applications	GEN-14000-1MHE
GX-0005	50-amp twist lock receptacle - Marine receptacle for routine marine applications	GEN-14000-1MHE

POWERED by HONDA.