

Semi-Trash Pumps

Frame:

- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Rubber isolators minimize vibration

Components:

- Silicon carbide mechanical seals
- Precision molded cast iron impeller and volute for reduced vibration and wear

Limited Warranty:

- 1 year Mi-T-M engine
- 2 year pump
- 3 year Honda engine



Suction and discharge kit, 70-0524

The Mi-T-M semi-trash pump features a 2-inch suction and discharge that handles solids up to $\frac{3}{4}$ -inch and is ideal for construction and agricultural applications.



2-Inch

MODEL NUMBER	SUCTION DISCHARGE SIZE	MAX. TOTAL HEAD	SUCTION LIFT	DISPLACEMENT/ENGINE	PSI	MAX. CAPACITY	FUEL TANK CAPACITY	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
WTP-S02-1MGH	2in.x2in.	115ft.	28ft.	118cc Honda GX120 OHV	50	9,720 gph	0.53 gallon	20.5x17x16.25in.	71 lb.	62 lb.
WTP-S02-1MGM ^A	2in.x2in.	115ft.	28ft.	136cc Mi-T-M OHV	50	9,720 gph	0.71 gallon	20.5x17x16.25in.	72 lb.	63 lb.
WTP-S02-CMGM [*]	2in.x2in.	115ft.	28ft.	136cc Mi-T-M OHV	50	9,720 gph	0.71 gallon	20.5x17x16.25in.	72 lb.	63 lb.

^AModel available in US only.^{*}Model available in US and Canada.
Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
15-0293	20-ft. x 2-in. green PVC hard suction hose with fittings	All models	19-0628	2-in. steel suction strainer with round openings	All models
15-0295	50-ft. x 2-in. blue PVC soft discharge hose	All models	70-0524	2-in. suction and discharge kit	All models