

Use the 3-inch semi-trash pump to remove unwanted water and small solid waste from your job site. Powered by one of two engines; a Honda OHV or a Mi-T-M OHV, this pump is ideal for construction and agricultural applications.

Semi-Trash Pumps

Frame:

- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Rubber isolators minimize vibration

Components:

- Silicon carbide mechanical seals
- Precision molded cast iron impeller and volute for reduced vibration and wear

Limited Warranty:

- 1 year Mi-T-M engine
- 2 year pump
- 3 year Honda engine



WTP-S03-2MGM



Suction and discharge kit, 70-0525

3-Inch

MODEL NUMBER	SUCTION DISCHARGE SIZE	MAX. TOTAL HEAD	SUCTION LIFT	DISPLACEMENT/ENGINE	PSI	MAX. CAPACITY	FUEL TANK CAPACITY	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
WTP-S03-1MGH	3in.x3in.	104ft.	28ft.	196cc Honda GX200 OHV	45	16,560 gph	0.83 gallon	21.25x17.25x18.25in.	82 lb.	73 lb.
WTP-S03-2MGM	3in.x3in.	104ft.	28ft.	212cc Mi-T-M OHV	45	16,560 gph	1.0 gallon	21.25x17.25x18.25in.	82 lb.	73 lb.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
15-0294	20-ft. x 3-in. green PVC hard suction hose with fittings	All models	19-0629	3-in. steel suction strainer with round openings	All models
15-0296	50-ft. x 3-in. blue PVC soft discharge hose	All models	70-0525	3-in. suction and discharge kit	All models