

The propane tank-top radiant heater is convenient, versatile and great for outdoor use. Simply connect to a standard 20 pound propane cylinder and heat your workspace for up to 48 hours. For use in open workshops, construction sites, farms and any other outdoor heating need.

Propane Tank-Top Radiant



MH-0030-IM10

Frame:

- Heavy-duty construction
- Rust-proof chrome emitter guard
- Rear burner safety guard

Heat Output:

- Variable heat control valve
- Clean, quiet, instant radiant heat

Components:

- Standard propane tank connection
- High efficiency heat reflector
- Hand wheel valve connection

Limited Warranty:

- 1 year

Certifications:

- CSA Certified - US and Canada

Important Notes:

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation

9,000 up to 32,000 BTU

MODEL NO.	MH-0015-IM10	MH-0030-IM10
HEAT OUTPUT (SINGLE BURNER)*	L-9,000 / M-12,000 / H-16,000 BTU	L-9,000 / M-12,000 / H-16,000 BTU
HEAT OUTPUT (DOUBLE BURNER)*	N/A	L-18,000 / M-24,000 / H-32,000 BTU
IGNITION TYPE	Match light	Match light
HEAT SETTINGS	3	6
PROPANE CYLINDER SIZE	20 lb.	20 lb.
MAX. OPERATING HOURS (20 LB. CYL.)*	L-48 / M-36 / H-27 hours	L-48 / M-18 / H-14 hours
SWIVEL BURNER HEAD	No	Yes
SAFETY SHUT-OFF VALVE	Yes	Yes
HEAT REGULATOR KNOB	Yes	Yes
MANIFOLD	Cast aluminum	Cast aluminum
DIMENSIONS (LxWxH)	8.4x7.4x12in.	17.5x5.5x12in.
SHIP WT.	3 lb.	6 lb.
NET WT.	2 lb.	5 lb.

*Heat output and operating hours have Low, Medium and High settings.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.