

# CA Aluminum Series | Gasoline Direct Drive

The CA Aluminum Series features a lightweight, corrosion-resistant aluminum frame and base plate with 1¼-inch tube handles, a patented vibration isolation plate and flat-free tires. Designed for mobility, this unit is capable of cleaning dirt and grime off any surface.



**SEE**  
...the future!



CA-2703-1MMK

## Pump

- Direct drive triplex piston AR, General or Mi-T-M pump with ceramic plungers
- Forged brass manifold
- Thermal relief valve
- In-line water strainer
- Stainless-steel and brass Mi-T-M unloader with adjustable pressure

## Frame

- Patented vibration isolation plate
- Aluminum frame and base plate with 1¼-inch tube handles
- Flat-free tires

## Unit Includes:

- Quick connect nozzles – 0°, 15° and 25°
- 50-foot x ¾-inch non-marking hose with quick connects, swivel and bend restrictors
- Insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 3500 and 4000-PSI models)



# CA Aluminum Series | Gasoline Direct Drive



**SEE**  
...the future!

Model Number	PSI	GPM	Displacement/Engine	Pump	Unloader	Lance	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CA-2403-1MMH	2400	2.4	196cc Honda GX200 OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMH	2700	2.4	196cc Honda GX200 OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMK	2700	2.4	208cc Kohler CH270 OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-3003-1MAH	3000	3.0	270cc Honda GX270 OHV	AR	Mi-T-M, adjustable pressure	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3003-1MAK	3000	3.0	277cc Kohler CH395 OHV	AR	Mi-T-M, adjustable pressure	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3504-1MAH	3500	3.5	389cc Honda GX390 OHV	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-3504-1MGH*	3500	4.0	389cc Honda GX390 OHV	General	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAH	4000	3.5	389cc Honda GX390 OHV	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAK	4000	3.5	429cc Kohler CH440 OHV	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MGH*	4000	4.0	389cc Honda GX390 OHV	General	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.

\*Model comes standard with external bypass system.

Options:		
Part Number	Description	Fits Models
CX-0005	<b>48-in. insulated dual lance</b> - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	All models
CX-0097	<b>External bypass system</b> - Allows more water into the system to protect from heat build-up	2400 to 2700-PSI models
CX-0098	<b>External bypass system</b> - Allows more water into the system to protect from heat build-up	3500 to 4000-PSI models except 1MGH
CX-0099	<b>External bypass system</b> - Allows more water into the system to protect from heat build-up	3000-PSI models

Accessories:		
Part Number	Description	Fits Models
50-0161	<b>High pressure detergent injector</b> - High pressure water mixes with detergent to clean even the heaviest build-up	All models
851-0338	<b>50-ft. x 3/8-in. non-marking hose</b> - For when you need extra hose for added mobility	All models
AW-8400-0021	<b>Low pressure detergent injector</b> - Allows the user to apply the recommended detergents	All models

POWERED by **HONDA**™