

CW Premium Series | Electric Belt Drive

Offering up to 5000-PSI of cleaning power, the electric CW Series is the perfect model for heavily-soiled commercial and industrial equipment that requires cleaning.



SEE
...the future!



CW-4004-1ME3 shown with 460V,
3-phase motor option, CX-0057

Pump

- Belt drive triplex piston General pump with ceramic plungers
- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection
- Stainless-steel and brass unloader with preset pressure (CW-4004 features a Mi-T-M unloader)

Frame

- Powder coated steel frame and base plate with tube handles
- Flat-free tires
- Enclosed belt guard

Motor

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 10-foot power cord

Component

- Heavy-duty dual clogged belt drive system

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors
- Insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 4000 and 5000-PSI models)

CW Premium Series | Electric Belt Drive



SEE
...the future!



NEMA L15-30P,
30-amp plug



NEMA 15-50P,
50-amp plug



NEMA 6-50P,
50-amp plug

Model Number	PSI	GPM	Horsepower/Motor	Pump	Unloader	Plug Type	Lance	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CW-2405-4ME1	2400	4.6	7.5 HP, 230V, 1Ø, 32.0A	General	Factory preset	NEMA 6-50P	36in.	46x28x30in.	345 lb.	333 lb.
CW-2405-4ME3*	2400	4.6	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	Factory preset	NEMA L15-30P	36in.	46x28x30in.	255 lb.	243 lb.
CW-3004-4ME1	3000	3.5	7.5 HP, 230V, 1Ø, 32.0A	General	Factory preset	NEMA 6-50P	36in.	46x28x30in.	350 lb.	338 lb.
CW-3004-4ME3*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	Factory preset	NEMA L15-30P	36in.	46x28x30in.	330 lb.	318 lb.
CW-3005-0ME1	3000	4.8	10.0 HP, 230V, 1Ø, 41.5A	General	Factory preset	NEMA 6-50P	36in.	45.5x32.5x30in.	470 lb.	396 lb.
CW-3005-0ME3*	3000	4.8	10.0 HP, 230V, 3Ø, 26.0A or 10.0 HP, 460V, 3Ø, 13.0A	General	Factory preset	NEMA 15-50P	36in.	45.5x32.5x30in.	450 lb.	376 lb.
CW-4004-1ME3	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	Mi-T-M, factory preset	NEMA 15-50P	48in.	45.5x32.5x30in.	505 lb.	431 lb.
CW-5004-0ME3*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	Factory preset	NEMA 15-50P	48in.	45.5x32.5x30in.	505 lb.	431 lb.

*460V motors available as options.

Options:		
Part Number	Description	Fits Models
CX-0003	460V on 8.0-HP, 3-phase models - For when you have 460V of power available	CW-2405-4ME3 & CW-3004-4ME3
CX-0005	48-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	All models
CX-0057	460V on 15.0-HP, 3-phase models - For when you have 460V of power available	CW-4004-1ME3 & CW-5004-0ME3
CX-0062	460V on 10.0-HP, 3-phase model - For when you have 460V of power available	CW-3005-0ME3
CX-0093	Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	CW-2405 & CW-3004 models
CX-0094	Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	CW-3005, CW-4004 & CW-5004 models

Accessories:		
Part Number	Description	Fits Models
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	All models
851-0317	50-ft. x ¾-in. non-marking hose - For when you need extra hose for added mobility	CW-5004-0ME3
851-0338	50-ft. x ¾-in. non-marking hose - For when you need extra hose for added mobility	2400 to 4000-PSI models
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	All models