

Dual-Axle Trailers

Trailer units are fully integrated and self-contained systems that are designed with a large water supply tank for working at remote sites where water is not accessible. The heavy-duty construction of the trailer and axle suspension provide an easy ride to ensure the longevity of your equipment. Add a high quality pressure washer and you have the power required to get large jobs done quickly wherever you may need to work.



SEE
...the future!



Features

- Swivel jack with pad
- Rubber mounted sealed lights
- Tanks are enclosed in a powder coated steel frame
- Will fit all Mi-T-M pressure washers
- Aluminum treadplate steps for access to water tanks
- Storage area located under the water tanks (AW-9000-0003 & AW-9000-0004 models)
- (2) 200-gallon water tanks are plumbed together (AW-9000-0003 & AW-9000-0004 models)

Accessories & Options

- Pressure washers
- Hose reels
- Back-flow preventers
- Trailer tank bypass
- Trailer hitches

AW-9000-0003 shown with HVS-3505-1H6G hot water pressure washer and hose reels (available as accessories)

Dual-Axle Trailers



SEE
...the future!

Model Number	Water Tank	Brakes	Coupler	Tires	Axles	Storage Area	Trailer Deck Plate	Angle Frame	Trailer Bed Dimensions	Gross Vehicle Wt.
AW-9000-0003	(2) 200-gallon	Surge	2in.	(4) ST205-75R 15in.	(2) 3,500 lb.	5ft.x4ft.x12in.	.25in. solid steel	3in.x4.25in.	5ft.x8.5ft.	7,000 lb.
AW-9000-0004	(2) 200-gallon	Electric	2in.	(4) ST205-75R 15in.	(2) 3,500 lb.	5ft.x4ft.x12in.	.25in. solid steel	3in.x4.25in.	5ft.x8.5ft.	7,000 lb.
AW-9000-0008	(1) 200-gallon	Surge	2in.	(4) ST205-75R 15in.	(2) 3,500 lb.	None	.25in. solid steel	3in.x4.25in.	5ft.x8.5ft.	7,000 lb.

Dual-Axle Trailer Accessories & Options:

High Pressure Hose Reels

These high pressure hose reels include a reel with jumper hose and mounting bracket.

TX-0001 (13-inch reel)

TX-0002 (16-inch reel)

Low Pressure Hose Reel

This low pressure hose reel includes a reel with mounting bracket and plumbing.

TX-0003 (16-inch reel)

Back-Flow Preventers

The back-flow preventer is required on trailer units in California.

TX-0011

- Adds the backflow preventer to dual-axle trailers, AW-9000-0003 and AW-9000-0004 that have the TX-0003 low pressure hose reel option
- Mounts to hose reel or inlet plumbing on trailer

Trailer Tank Bypass

TX-0004 (Used on trailers with HDS & HDC Series pressure washers)

TX-0005 (Used on trailers with HVS Series pressure washers)

- Removes the float system, while adding the necessary plumbing
- Water bypasses back to water tank

Replacement Hose Reel Parts

When adding hose reels to the trailers, use the following jumper hose and mounting bracket.

15-0159 (Jumper hose)

13-0179A01 (Mounting bracket)

50-0195 (13-inch hose reel, 150-foot max. hose length, rated for 4000-PSI units and lower)

50-0196 (16-inch hose reel, 200-foot max. hose length, rated for 4000-PSI units and lower)

Trailer Hitches

This specially designed heavy-duty, 2-inch trailer hitch has a pin-style fastener trailer coupler and hinged ball socket with visual indication of proper closure around the ball - all to ensure a quick, easy and secure hook-up. Includes hitch with brackets and hardware.

TX-0010 (For use with AW-9000-0004 trailer)