

HDB Series | Gasoline/Diesel Belt Drive

The HDB Series is a small, compact mini skid that installs easily in tight spaces.



SEE
...the future!



Pump

- Belt drive triplex piston General pump
- Low pressure detergent injector

Engine

- Performance-proven gasoline engine or Kohler diesel engine with electric start – battery not included

Frame

- Powder coated steel square tube skid frame
- Stainless-steel removable front panel
- Optional wheel kit with locking tire brake, four tires and solid steel threaded axles

Components

- Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil
- 12V Beckett burner - no need for a generator – battery not included
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)

Miscellaneous

- Adjustable thermostat
- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch high pressure hose
- Adjustable pressure insulated dual lance
- Insulated trigger gun with safety lock-off



HDB-3005-0K6G shown with optional steam and hour meter



HDB Series | Gasoline/Diesel Belt Drive



SEE
...the future!

Model Number	PSI	GPM	Horsepower/Displacement/Engine	Engine Fuel Tank Capacity	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HDB-3004-0K7G*	3000	3.9	9.1 HP Kohler KD440 OHV Diesel	1.3 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	745 lb.	626 lb.
HDB-3004-0H6G	3000	3.9	389cc Honda GX390 OHV	1.7 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	685 lb.	566 lb.
HDB-3005-0V6G	3000	4.8	480cc Vanguard OHV	10.0 gallons	10.0 gallons	2.76 gph	386,400	53.5x28.75x42in.	720 lb.	601 lb.
HDB-3005-0K6G	3000	4.8	624cc Kohler CH620 OHV Gasoline	10.0 gallons	10.0 gallons	2.76 gph	386,400	53.5x28.75x42in.	736 lb.	617 lb.

*Diesel Model

Options:		
Part Number	Description	Fits Models
HX-0156	Hour meter - Displays the number of hours unit has been in operation	All models
HX-0176	250°F steam - Increases outlet temperature to 250°F, #3 nozzle	HDB-3004 models
HX-0220	High pressure chemical (K7) - Adjustable high pressure chemical, includes float tank	All models
HX-0221*	High pressure chemical (Trapping unloader) - Adjustable high pressure chemical, includes float tank	All models
HX-0222	Panel engine key switch - Moves engine key switch from engine to front panel	HDB-3005-0V6G
HX-0224	250°F steam - Increases outlet temperature to 250°F, includes steam nozzle and valve	HDB-3005 models
HX-0225	Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas	All models
HX-0226	Three-way ball valve - Allows the pressure washer to be operated from garden hose, float tank or trailer supply by adjusting ball level valve	All models

*HX-0225 trapping unloader is required when ordering the HX-0221 high pressure chemical option.

Accessories:		
Part Number	Description	Fits Models
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	Gasket (For 50-0170) - Seals between 50-0170 stack adapter and boiler housing	All models
AW-5740-0014	Wheel kit - Four rubber wheels allows unit to become portable	All models
AW-5740-0015	Caster wheel kit - Includes two caster wheels and two rubber wheels for easier movement on flat surfaces	All models
AW-6000-1006	Hot water skid equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, Mi-T-M logo	All models
AW-6000-1007	Hot water skid equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, no logo	All models

POWERED by **HONDA**™