

# HDC Series | Gasoline Belt Drive

*The HDC Series is the most affordable and efficient skid on the market today. The best buy for a quick return on investment.*



**SEE**  
...the future!



## Pump

- Belt drive triplex piston AR or General pump with ceramic plungers
- Adjustable high pressure detergent injector

## Engine

- Performance-proven industrial gasoline engine with electric start – battery not included

## Frame

- Heavy-duty powder coated steel square tube skid frame
- Stainless-steel coil wrap prevents rusting

## Components

- Stainless-steel wrap heat exchanger with 1/2-inch schedule 80 pipe coil
- Polyethylene engine and burner fuel tanks
- 12V Beckett burner - no need for a generator – battery not included
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- Large polyethylene float tank

## Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

## Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose
- Adjustable pressure insulated dual lance
- Insulated trigger gun with safety lock-off



*HDC-3505-0K6G shown with optional adjustable temperature control, HX-0212*



# HDC Series | Gasoline Belt Drive



**SEE**  
...the future!

Model Number	PSI	GPM	Displacement/Engine	Pump	Engine Fuel Tank Capacity	Burner Fuel Tank Capacity	Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HDC-3005-0K6G	3000	4.8	624cc Kohler CH620 OHV	General	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-3005-0V6G	3000	4.8	480cc Vanguard OHV	General	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-3505-1H6G	3500	4.7	GX630 Honda OHV	General	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-3505-0K6G*	3500	4.7	624cc Kohler CH620 OHV	General	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-4004-1H6A	4000	4.0	GX630 Honda OHV	AR	10.0 gallons	10.0 gallons	2.45 gph	343,000	50x34x46in.	844 lb.	725 lb.

\*Higher performance 624cc Kohler engine.

Options:		
Part Number	Description	Fits Models
HX-0130	<b>Three-way ball valve</b> - Allows the pressure washer to be operated from garden hose, float tank or trailer supply by adjusting ball level valve	All models
HX-0147	<b>Four-point lifting capability</b> - Allows unit to be lifted by a crane	All models
HX-0156	<b>Hour meter</b> - Displays the number of hours unit has been in operation	All models
HX-0200	<b>Trapping unloader</b> - For hose runs longer than 50-feet and for cleaning elevated areas	HDC-3005 & HDC-3505 models
HX-0212	<b>Adjustable temperature control</b> - Operator is able to adjust outlet water temperature between 96°F–250°F	All models
HX-0229	<b>Clutch drive pump</b> - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, changes GPM to 4.3 when added to the unit	3000-PSI models
HX-0230	<b>Clutch drive pump</b> - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, changes GPM to 4.2 when added to the unit	3500-PSI models
HX-0266	<b>Clutch drive pump</b> - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, standard flow rate	HDC-3005 & HDC-3505 models

Accessories:		
Part Number	Description	Fits Models
50-0170	<b>Stack adapter</b> - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	<b>Gasket (For 50-0170)</b> - Seals between 50-0170 stack adapter and boiler housing	All models
AW-5740-0000	<b>Wheel kit</b> - Allows unit to become portable	All models
AW-6000-1006	<b>Hot water skid equipment cover</b> - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, Mi-T-M logo	All models
AW-6000-1007	<b>Hot water skid equipment cover</b> - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, no logo	All models

POWERED BY **HONDA**™