

# HDD Series | Gasoline Direct Drive

The HDD Series is a compact versatile machine, with a fold down handle and optional wheel kit, this machine fits through a 30-inch doorway.



**SEE**  
...the future!



## Pump

- Direct drive triplex piston AR pump
- Low pressure detergent injector

## Engine

- Performance-proven gasoline engine

## Frame

- Powder coated steel square tube skid frame
- Stainless-steel removable front panel
- Optional wheel kit with locking tire brake, four tires and solid steel threaded axles

## Components

- Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil
- 12V Beckett burner - no need for a generator – battery not included
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)

## Miscellaneous

- Adjustable thermostat
- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

## Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch high pressure hose
- Adjustable pressure insulated dual lance
- Insulated trigger gun with safety lock-off

HDD-3504-0H6A shown with optional hour meter



# HDD Series | Gasoline Direct Drive



**SEE**  
...the future!

Model Number	PSI	GPM	Displacement/Engine	Engine Fuel Tank Capacity	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HDD-3504-0H6A	3500	3.3	389cc Honda GX390 OHV	1.7 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	652 lb.	533 lb.
HDD-3804-0V6A	3800	3.8	480cc Vanguard OHV	10.0 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	677 lb.	558 lb.

Options:		
Part Number	Description	Fits Models
HX-0156	Hour meter - Displays the number of hours unit has been in operation	All models
HX-0172	250°F steam - Increases outlet temperature to 250°F, #3 nozzle	All models
HX-0221	High pressure chemical (Trapping unloader) - Adjustable high pressure chemical, includes float tank	All models
HX-0222	Panel engine key switch - Moves engine key switch from engine to front panel	HDD-3804-0V6A
HX-0225	Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas	All models
HX-0226	Three-way ball valve - Allows the pressure washer to be operated from garden hose, float tank or trailer supply by adjusting ball level valve	All models

Accessories:		
Part Number	Description	Fits Models
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	Gasket (For 50-0170) - Seals between 50-0170 stack adapter and boiler housing	All models
AW-5740-0014	Wheel kit - Four rubber wheels allows unit to become portable	All models
AW-5740-0015	Caster wheel kit - Includes two caster wheels and two rubber wheels for easier movement on flat surfaces	All models
AW-6000-1006	Hot water skid equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, Mi-T-M logo	All models
AW-6000-1007	Hot water skid equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, no logo	All models

POWERED by **HONDA**™