

HHM Series | Diesel/Oil-Heated Heater Module

The HHM Series is an electric-powered, diesel/oil-heated hot water heater module that is the perfect add-on to the cold water pressure washer you already have in operation.



SEE
...the future!



Frame

- Powder coated steel frame assembly
- Stainless-steel coil wrap
- Flat-free tires

Components

- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Horizontal schedule 80 pipe coil heat exchanger
- 35-foot power cord with GFCI
- Adjustable thermostat

Miscellaneous

- 250°F maximum outlet temperature (150°F temperature rise at 4.0-GPM)

Unit Includes:

- 12-foot x 3/4-inch jumper hose with quick connects to hook up to existing pressure washer



HHM-3506-0E10



GFCI
15-amp plug



CSA
CERTIFIED



Model Number	PSI	GPM	Electrical Voltage/Phase/Amp	Burner Fuel Consumption	Diesel BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHM-3506-0E10	3500	6.0	115V, 1Ø, 3.2A	2.76 gph	386,400	56.5x30x41.5in.	543 lb.	423 lb.

Option:

Part Number	Description	Fits Model
HX-0171	Skid feet - Stationary applications	HHM-3506-0E10

Accessories:

Part Number	Description	Fits Model
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	HHM-3506-0E10
850-0324	Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing	HHM-3506-0E10