

JCW Series | Gasoline Belt Drive

Built with an all-steel frame and base plate, the JCW Series belt-driven pressure washer can handle the toughest environments.



SEE
...the future!



JCW-3504-2MHB

Pump

- Belt drive triplex piston AR pump with ceramic plungers
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection
- Stainless-steel and brass unloader with adjustable pressure (3000, 3500 and 4000-PSI models feature a Mi-T-M unloader)

Frame

- Powder coated steel frame and base plate with 1¼-inch tube handles
- Two-piece belt guard for quick access to belts
- Flat-free tires

Engine

- Performance-proven Honda OHV engine with low-oil shutdown

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x ¾-inch non-marking hose with quick connects, swivel and bend restrictors
- Insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 3500 and 4000-PSI models)



JCW Series | Gasoline Belt Drive



SEE
...the future!

Model Number	PSI	GPM	Displacement/Engine	Pump	Unloader	Lance	Dimensions (LxWxH)	Ship Wt.	Net Wt.
JCW-2403-0MHB	2400	2.8	196cc Honda GX200 OHV	AR	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-2703-0MHB	2700	2.4	196cc Honda GX200 OHV	AR	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-3003-2MHB	3000	3.0	270cc Honda GX270 OHV	AR	Mi-T-M, adjustable pressure	36in.	39.5x28.5x26in.	232 lb.	178 lb.
JCW-3504-2MHB	3500	3.7	389cc Honda GX390 OHV	AR	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	245 lb.	191 lb.
JCW-4004-2MHB	4000	3.5	389cc Honda GX390 OHV	AR	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	249 lb.	195 lb.

Options:		
Part Number	Description	Fits Models
CX-0005	48-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	All models
CX-0082	External bypass system - Allows more water into the system to protect from heat build-up; attaches to pump	3000 to 4000-PSI models
CX-0085	External bypass system - Allows more water into the system to protect from heat build-up; attaches to base plate	3000 to 4000-PSI models

Accessories:		
Part Number	Description	Fits Models
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	All models
851-0338	50-ft. x 3/8-in. non-marking hose - For when you need extra hose for added mobility	All models
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	All models

POWERED by **HONDA**™