JP Series | Gasoline Direct Drive

The powerful gasoline direct drive JP Series is designed for excellent balance and mobility. It is highly recommended for contractor jobs.







Pump

- Direct drive triplex piston AR or Mi-T-M pump with ceramic plungers
- Forged brass manifold
- Thermal relief valve
- In-line water strainer
- Stainless-steel and brass Mi-T-M unloader with adjustable pressure

Frame

- Powder coated steel frame and base plate with 11/4-inch tube handles
- Flat-free tires

Engine

- Performance-proven Honda OHV engine with low-oil shutdown

Unit Includes:

- Quick connect nozzles 0°, 15° and 25°
- 50-foot x %-inch non-marking hose with quick connects, swivel and bend restrictors
- Insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 3500 and 4000-PSI models)



JP Series | Gasoline Direct Drive





| Model Number | PSI | GPM | Displacement/Engine | Pump | Unloader | Lance | Dimensions (LxWxH) | Ship Wt. | Net Wt. |
|--------------|------|-----|-----------------------|--------|-----------------------------|-------|--------------------|----------|---------|
| JP-2403-3MHB | 2400 | 2.4 | 196cc Honda GX200 OHV | Mi-T-M | Mi-T-M, adjustable pressure | 36in. | 37x21x24.5in. | 100 lb. | 75 lb. |
| JP-2703-3MHB | 2700 | 2.4 | 196cc Honda GX200 OHV | Mi-T-M | Mi-T-M, adjustable pressure | 36in. | 37x21x24.5in. | 110 lb. | 85 lb. |
| JP-3003-3MHB | 3000 | 3.0 | 270cc Honda GX270 OHV | AR | Mi-T-M, adjustable pressure | 36in. | 40x22.5x24.5in. | 180 lb. | 130 lb. |
| JP-3504-3MHB | 3500 | 3.5 | 389cc Honda GX390 OHV | AR | Mi-T-M, adjustable pressure | 48in. | 40x22.5x24.5in. | 192 lb. | 142 lb. |
| JP-4004-3MHB | 4000 | 3.5 | 389cc Honda GX390 OHV | AR | Mi-T-M, adjustable pressure | 48in. | 40x22.5x24.5in. | 192 lb. | 142 lb. |

| Options: | | | | | | |
|-------------|--|-------------------------|--|--|--|--|
| Part Number | Description | Fits Models | | | | |
| CX-0005 | 48-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips | All models | | | | |
| CX-0083 | External bypass system - Allows more water into the system to protect from heat build-up | 2400 to 2700-PSI models | | | | |
| CX-0084 | External bypass system - Allows more water into the system to protect from heat build-up | 3500 to 4000-PSI models | | | | |

| Accessories: | | | | | | |
|--------------|---|-------------|--|--|--|--|
| Part Number | Description | Fits Models | | | | |
| 50-0161 | High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up | All models | | | | |
| 851-0338 | 50-ft. x %-in. non-marking hose - For when you need extra hose for added mobility | All models | | | | |
| AW-8400-0021 | Low pressure detergent injector - Allows the user to apply the recommended detergents | All models | | | | |

POWERED by HONDA