

# PWR Series | Recovery & Recycle System

The PWR Series allows for wash water to be reclaimed on the job site. Water is reclaimed by using the 20-foot water berm (included) to stop water from flowing down a drain or away from your area. The suction head draws wash water into a holding chamber where a second pump forces the water through an optional 10-micron bag filter before returning it to the holding tank for reuse or proper disposal.



**SEE**  
...the future!

**Features:**

- 1/3 HP transfer pump
- Oil absorbing boom/sock
- Vacuum tank drain
- 3-stage vacuum motor
- Stainless-steel suction head
- Cam lock fittings
- 50-foot vacuum hose
- 55-gallon capacity
- 20-foot water berm



PWR-10-OME1 shown with standard accessories: oil absorbing boom, 33-0529; stainless-steel suction head, 21-0306; 50-ft. vacuum hose and 20-ft. water berm, 33-0520; also shown with dual filters option, WX-0109

Model Number	Vacuum Motor	Tank Capacity	Filter Pump	Water Berm	Dimensions (LxWxH)	Ship Wt.	Net Wt.
PWR-10-OME1	3-stage, 1500W, 12.5A full load	55-gallons	1/3 HP, 8.0A, 120VAC, 60Hz, 10	6in.x20ft.	48x42x60in.	340 lb.	290 lb.

**Options:**

Part Number	Description	Fits Model
WX-0106	Wheel kit - Includes two flat-free tires, powder coated steel frame and handle	PWR-10-OME1
WX-0108	Single bag filter - Uses 10-micron bag #19-0249	PWR-10-OME1
WX-0109	Dual filters - Uses 10-micron bag #19-0249 and 50-micron bag #19-0267	PWR-10-OME1
WX-0129	Dual filters for PWR-10-OME1 trailer-mount package	PWR-10-OME1

**Accessories:**

Part Number	Description	Fits Model
19-0249	10-micron filter bag - 1 qty., fits inside WX-0108 & WX-0109 filters	PWR-10-OME1
19-0267	50-micron filter bag - 1 qty., fits inside WX-0109 filter	PWR-10-OME1
21-0306	Stainless-steel suction head	PWR-10-OME1
33-0520	Water berm - 6-in. x 20-ft.	PWR-10-OME1
33-0529	Oil absorbing boom - Oil sock for inside of tank	PWR-10-OME1
855-0057	50-ft. extension hose - Can have up to 100-ft. of extension hose	PWR-10-OME1

# PWR Series | Portable Water Recovery Trailer Packages

## PWR Series Trailer Packages Include:

- Portable Water Recovery Trailer, AW-9000-0010
- PWR-10-0ME1 with WX-0129 Option
- Hot Water Pressure Washer, choose from HVS-3505-1H6G or HDS-3505-1H6G

### Portable Water Recovery Trailer – AW-9000-0010

- 5-foot x 8½-foot dual-axle trailer
- 200-gallon water tank enclosed in powder coated steel frame
- Swivel jack with stand
- Rubber mounted sealed lights
- 50-foot inlet garden hose with hose reel
- 100-foot high pressure hose with hose reel
- Tank feed for pressure washer
- Option to direct feed water from inlet hose reel

### Hot Water Pressure Washer – HVS-3505-1H6G with HX-0252 Option for Trailer

- 3500 PSI @ 4.2 GPM
- GX630 Honda OHV gasoline engine
- Belt drive triplex clutch driven General pump
- Powder coated steel protective square tubing roll cage frame assembly
- Powder coated steel coil wrap and control panel
- Trailer tank feed
- 80-mesh inlet Y-strainer
- Generator wired for burner and PWR-10-0ME1 with WX-0129 option
- Consult dealer for additional options available for the HVS-3505-1H6G

### PWR-10-0ME1 with WX-0129 Option for Trailer

*Includes all standard PWR Series features, as well as:*

- Mounts to AW-9000-0010 trailer
- 2 bag filters – 10- and 50-micron (other bags are available down to 1.0-micron, consult dealer)
- Automatic discharge to outlet valve for reuse or discharge

### Hot Water Pressure Washer – HDS-3505-1H6G with HX-0253 Option for Trailer

- 3500 PSI @ 4.2 GPM
- GX630 Honda OHV gasoline engine
- Belt drive triplex clutch driven General pump
- Powder coated steel protective square tubing roll cage frame assembly
- Stainless-steel coil wrap and control panel
- Trailer tank feed
- 80-mesh inlet Y-strainer
- Generator wired for burner and PWR-10-0ME1 with WX-0129 option
- Consult dealer for additional options available for the HDS-3505-1H6G



**SEE**  
...the future!



*PWR-10-0ME1 with WX-0129 option for trailer shown with portable water recovery trailer, AW-9000-0010; HDS-3505-1H6G with HX-0253 option for trailer*