

# Rotary Screw | Single Stage Gasoline

The portable gas-driven rotary screw air compressor is capable of producing 115 CFM @ 100 PSI, enough to power a 90 pound breaker! Widely used on a variety of construction sites to run multiple air tools.



**SEE**  
...the future!



## Compressor Pump

- Integrated air/oil separator
- Integrated thermostatic bypass valve
- Integrated oil filter
- Poly Chain® belt drive system
- Easy-to-read oil level indicator
- High oil temperature shutdown

## Engine

- Electric start - battery and cables included
- Low-oil level shutdown

## Frame

- Powder coated steel frame with 1¼-inch roll cage, handle, 4-point lifting hook, winch point and tie-down anchors
- 15-inch pneumatic tires

## Components

- 10½-gallon aluminized steel fuel tank
- Oil cooler with guard
- Pressure gauge
- Ball valve controlled ¾-inch outlet
- Pilot valve varies engine RPM based on air demand



AR1-PK37-M



Air/oil separator, 19-0279; oil filter, 19-0278; and RotorLub™ 8000, AW-2200-0004 and AW-2200-0005

Model Number	CFM @ PSI	Displacement/Engine	Compressor	Engine Idle Control	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AR1-PK37-M	115 @ 100	999cc Kohler CH1000 OHV	Single stage, rotary screw	Pneumatic	50.75x30.5x43.5in.	770 lb.	698 lb.

## Accessories & Options:

Part Number	Description	Fits Model
19-0278	Oil filter - Spin-on/spin-off filter	AR1-PK37-M
19-0279	Air/oil separator - Separates the oil from the air; minimizes lubricant carry-over	AR1-PK37-M
AW-2200-0001	Wye ball valve assembly - Allows the user to hook up two air hoses or two air tools instead of one	AR1-PK37-M
AW-2200-0002	Water separator assembly - Filters water from the outlet air	AR1-PK37-M
AW-2200-0003	Pressure regulator assembly - Regulates the outlet air pressure from 0 to 120-PSI	AR1-PK37-M
AW-2200-0004	Champion RotorLub™ 8000, 5-gallon pail - Rotary screw lubricant	AR1-PK37-M
AW-2200-0005	Champion RotorLub™ 8000, 1-gallon bottle - Rotary screw lubricant	AR1-PK37-M
AX-0076	Skid feet - Stationary applications	AR1-PK37-M