

# Work Pro<sup>®</sup> Series | Single Stage Electric/Gasoline

The high performing Work Pro<sup>®</sup> Series single stage electric or gasoline air compressors offer easy to use components and portability for the serious do-it-yourselfer and professional contractor.



**SEE**  
...the future!



AM1-PE02-05M



NEMA 5-15P,  
15-amp plug



CSA  
CERTIFIED  
AM1-HE02-04M  
AM1-PE02-05M

**Compressor Pump**

- Oil lubricated aluminum crankcase
- Copper discharge hose (Electric models)
- Stainless-steel braided discharge hose (Gasoline models)
- Cartridge air filter

**Motor**

- Thermal overload motor protection

**Frame**

- Powder coated tank design
- Protective pump/motor housing

**Components**

- Regulator and two gauges for tank and outlet pressure
- Drain and pressure relief valves
- Industrial interchange quick connect fittings (Electric models)
- Start/stop control set at 95 to 125-PSI

Electric Models	CFM @ PSI	Horsepower/Motor	Compressor	Cylinder	Tank Size	Type	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM1-HE15-03M	3.0 @ 90	1.5 HP, 120V, 15.0A	Single stage	Cast iron	3-gallon	Hand carry	NEMA 5-15P	22.5x10.5x22.25in.	46 lb.	41 lb.
AM1-HE02-04M	4.2 @ 90	2.0 HP, 120V, 15.0A	Single stage	Cast iron	4-gallon	Hand carry	NEMA 5-15P	21.5x16x15.75in.	68 lb.	60 lb.
AM1-PE02-05M	4.2 @ 90	2.0 HP, 120V, 15.0A	Single stage	Cast iron	5-gallon	Portable	NEMA 5-15P	19.75x19x33.5in.	79 lb.	69 lb.

Gasoline Models	CFM @ PSI	Displacement/Engine	Compressor	Tank Size	Engine Idle Control	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM1-HH04-05WP	4.8 @ 90	118cc Honda GX120 OHV	Single stage, aluminum	5-gallon	Pneumatic	21x17.25x21.75in.	85 lb.	77 lb.
AM1-HM04-05WP	4.8 @ 90	136cc Mi-T-M OHV	Single stage, aluminum	5-gallon	Cable throttle	21x17.25x21.75in.	85 lb.	77 lb.

Accessory:		
Part Number	Description	Fits Models
70-0357	Engine oil drain extension - 14-inch flexible drain hose makes oil changes clean and easy	AM1-HH04-05WP & AM1-HM04-05WP