

3000 & 5000-Watt Gasoline

Featuring an easy access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles; this portable generator provides power for most industrial and contractor needs.

Alternator:

- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame:

- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Angled isolator design features four neoprene isolators

Components:

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone mufflers
- Heavy-duty industrial air cleaner

Miscellaneous:


- USDA/USFS-approved spark arrestors

Limited Warranties:

- 2 year alternator
- 3 year Honda & Kohler engines
- 5 year Subaru engine

Certifications:

- CSA Certified



GFCI 5-20R



NEMA L14-20R
120V/240V



NEMA L5-30R
120VAC

To see more online, scan here or go to www.mitm.com



GEN-5000-OMSO

MODEL NO.	GEN-3000-1MH0 / GEN-3000-1MK0	GEN-5000-0MH0 / GEN-5000-0MK0 / GEN-5000-0MS0
MAX. AC OUTPUT	3000 watts	5000 watts
RATED AC OUTPUT	2450 watts	4400 watts
DISPLACEMENT/ENGINE	163cc Honda OHV / 208cc Kohler OHV	270cc Honda OHV / 277cc Kohler OHV / 287cc Subaru OHC
ALTERNATOR	Brushless 120V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	25.0	41.7/20.8
CONT. AMPS (120V/240V)	20.4	36.7/18.3
RECEPTACLES	(1) 120V, 20A GFCI duplex	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock
CIRCUIT BREAKERS	(1) 20A push-button	(2) 20A toggle circuit breaker, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole
RATED SPEED	3600 RPM	3600 RPM
DECIBEL RATING	74.8	73.8
FUEL CAPACITY	2.6 gallons	5.7 gallons
RUN TIME (AT FULL LOAD)	7.4 hours	6.8 hours
FUEL SHUT-OFF VALVE	Yes	Yes
FUEL GAUGE	Yes, easy-to-read	Yes, easy-to-read
FULL POWER SWITCH	No	Yes
DIMENSIONS (LxWxH)	25x18x18in.	29x19.75x22.5in.
SHIP WT.	146 lb.	198 lb.
NET WT.	130 lb.	176 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	5000-watt models	AW-5740-0009	Wheel kit	5000-watt models
AW-5090-0003	Lifting hook	5000-watt models	GX-0004	Hour meter	5000-watt models