

Designed for the serious contractor with multiple voltage applications and power needs. This unit features a wraparound frame making it a must for every jobsite.



GEN-8000-0MKO

6000, 7500 & 8000-Watt

Gasoline

Alternator:

- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame:

- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Angled isolator design features four neoprene isolators

Components:

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone mufflers
- Fuel shut-off valve
- Easy-to-read fuel gauge
- Idle control
- Voltmeter/hour meter
- Heavy-duty industrial air cleaner

Miscellaneous:

- USDA/USFS-approved spark arrestors

Limited Warranties:


- 2 year alternator
- 3 year Honda & Kohler engines
- 5 year Subaru engine

To see more online, scan here or go to www.mitm.com



Certifications:

- CSA Certified



GFCI 5-20R
All Models



NEMA L14-20R
120V/240V
GEN-6000
Models



NEMA L14-30R
120V/240V
GEN-7500 &
8000 Models



NEMA L5-30R
120VAC
All Models

| MODEL NO. | GEN-6000-0MHO* / GEN-6000-0MKO / GEN-6000-0MSO* | GEN-7500-0MHO* | GEN-8000-0MKO* / GEN-8000-0MSO* |
|-------------------------|---|---|---|
| MAX. AC OUTPUT | 6000 watts | 7500 watts | 8000 watts |
| RATED AC OUTPUT | 5000 watts | 6500 watts | 6900 watts |
| DISPLACEMENT/ENGINE | 389cc Honda OHV / 429cc Kohler OHV / 404cc Subaru OHC | 389cc Honda OHV | 429cc Kohler OHV / 404cc Subaru OHC |
| ALTERNATOR | Brushless 120V/240V, 60Hz | Brushless 120V/240V, 60Hz | Brushless 120V/240V, 60Hz |
| MAX. AMPS (120V/240V) | 50.0/25.0 | 62.5/31.25 | 66.7/33.3 |
| CONT. AMPS (120V/240V) | 41.7/20.8 | 54.2/27.1 | 57.5/28.75 |
| RECEPTACLES | (2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock | (2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock | (2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock |
| CIRCUIT BREAKERS | (1) Main circuit breaker (2) 20A toggle circuit breaker, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole | (2) 20A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole | (2) 20A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole |
| RATED SPEED | 3600 RPM | 3600 RPM | 3600 RPM |
| DECIBEL RATING | 77.1 / 77.1 / 77.4 | 80.0 | 78.2 |
| FUEL CAPACITY | 7.3 gallons | 7.3 gallons | 7.3 gallons |
| RUN TIME (AT FULL LOAD) | 8.0 hours / 8.0 hours / 7.9 hours | 6.9 hours | 6.9 hours |
| DIMENSIONS (LxWxH) | 29x24.4x22.5in. | 29x24.4x22.5in. | 29x24.4x22.5in. |
| SHIP WT. | 232 lb. | 255 lb. | 245 lb. |
| NET WT. | 210 lb. | 233 lb. | 233 lb. |

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

*Available with electric start - battery included.

Accessories:

| PART NUMBER | DESCRIPTION | FITS MODELS | PART NUMBER | DESCRIPTION | FITS MODELS |
|--------------|----------------------|-------------|--------------|-----------------|-------------|
| 32-0915 | RV generator adapter | All models | AW-5740-0010 | Wheel kit | All models |
| AW-5090-0004 | Lifting hook | All models | AW-6000-1002 | Equipment cover | All models |