

13000 & 14000-Watt

Gasoline

This portable generator is built to withstand the most demanding work conditions and can easily be transported from jobsite to jobsite.

Alternator:

- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame:

- Reinforced 1¼-inch powder coated steel tube frame
- Flat-free tires

Components:

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone mufflers
- Easy-to-read fuel gauge
- Idle control
- Voltmeter/hour meter
- Heavy-duty industrial air cleaner

Miscellaneous:

- USDA/USFS-approved spark arrestors

Limited Warranties:

- 2 year alternator
- 3 year Honda engine
- 5 year Subaru engine


Certifications:

- CSA Certified



GEN-14000-1MHE

To see more online, scan here or go to www.mitm.com



GFCI 5-20R



NEMA L14-30R
120V/240V



NEMA 14-50R
50A



NEMA L5-30R
120VAC



GX-0005 option
CS6369A
50A twist lock
receptacle

MODEL NO.	GEN-13000-1MSE	GEN-14000-1MHE
MAX. AC OUTPUT	13000 watts	14000 watts
RATED AC OUTPUT	11500 watts	12000 watts
DISPLACEMENT/ENGINE	650cc Subaru OHV with electric start - battery included	688cc Honda OHV with electric start - battery included
FREQUENCY/VOLTAGE	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	108.3/54.2	116.7/58.3
CONT. AMPS (120V/240V)	95.8/47.9	100.0/50.0
RECEPTACLES	(2) 120V, 20A GFCI duplex / (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock / (1) 120V/240V, 50A	(2) 120V, 20A GFCI duplex / (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock / (1) 120V/240V, 50A
CIRCUIT BREAKERS	(2) 20A toggle circuit breaker, single pole / (1) 30A toggle circuit breaker, single pole / (1) 30A toggle circuit breaker, double pole / (1) 50A toggle circuit breaker, double pole	(2) 20A toggle circuit breaker, single pole / (1) 30A toggle circuit breaker, single pole / (1) 30A toggle circuit breaker, double pole / (1) 50A toggle circuit breaker, double pole
RATED SPEED	3600 RPM	3600 RPM
DECIBEL RATING	77.5	77.5
FUEL CAPACITY	13.2 gallons	13.2 gallons
RUN TIME (AT FULL LOAD)	8.8 hours	8.0 hours
DIMENSIONS (LxWxH)	31.5x30.5x37.5in.	31.5x30.5x37.5in.
SHIP WT.	573 lb.	568 lb.
NET WT.	513 lb.	508 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adaptor	All models	GX-0003	Skid feet	All models
AW-6000-1002	Equipment cover	All models	GX-0005	50-amp twist lock receptacle	All models